

# BeneFusion eSP Vet

Syringe Pump

Datasheet



## Physical Specifications

Weight	≤ 1.6kg
Size	≤ 257x 150 x73mm
Screen	3.5 inch touchscreen TFT color LCD, 200x400 pixels
Brightness	1-8 levels, adjustable
Display	Infusion status(drug name, major infusion parameters, real-time pressure status) System status information(alarm information, infusion mode, battery status, relayed status, syringe brand or bed number)
Indicator on the door	Infusion status indicator

## Parameters Specifications

Accuracy	≤ ±1.8%
Mode	Rate mode, Dose Mode, Dose Time Mode, Time mode, Sequential Mode, Intermittent Mode, Loading Dose Mode, Ramp Mode, Micro-infusion Mode
Flow rate	0.01-2300ml/h
Increment	0.01ml/h(0.01-99.99ml/h),0.1ml/h(100.0-999.9ml/h),1ml/h(1000-2300ml/h)
Preset volume (VTBI)	0.01 ml -9999.99 ml,increment: 0.01mL
Preset time	00:00:01-99:59:59
Accumulated volume	0.00 ml - 99999.99 ml
KVO	0.01 to 5.0ml/h, increment: 0.01ml/h
Purge rate	0.01-2300ml/h
Bolus rate	0.01-2300ml/h (automatic or manual)
Occlusion detection	50-1125mmHg (15 levels selectable, respectively are 50, 150, 225, 300, 375, 450, 525, 600, 675, 750, 825, 900, 975, 1050, 1125mmHg) default is 450mmHg, Pre-alarm: an alert will pop out when the pressure is continuously going up

Auto-restart: On/Off, restart the infusion when the occlusion pressure is reduced.

4 units of pressure selectable:

mmHg/kPa/bar/psi

Anti-bolus	Unexpected bolus reduced when the occlusion occurs
Dose rate units	ng/kg/min, ng/kg/h,ng/kg/24h, ug/kg/min, ug/kg/h,ug/kg/24h, mg/kg/min, mg/kg/h, mg/kg/24h,g/kg/min, g/kg/h, g/kg/24h, mU/kg/min, mU/kg/h, mU/kg/24h, U/kg/min, U/kg/h, U/kg/24h,kU/kg/min, kU/kg/h, kU/kg/24h, EU/kg/min, EU/kg/h, EU/kg/24h, mmol/kg/min, mmol/kg/h, mmol/kg/24h, mol/kg/min, mol/kg/h, mol/kg/24h, mcal/kg/min, mcal/kg/h,mcal/kg/24h,cal/kg/min, cal/kg/h,cal/kg/24h,kcal/kg/min, kcal/kg/h, kcal/kg/24h, mEq/kg/min, mEq/kg/h, mEq/kg/24h

Auto-lock time 1 -5 minutes selectable, ON/OFF switchable

Drug library Up to 5000 drugs,30 categories, support color-coding drug name

History log Up to 3500 events

Volume collection Available in 4 methods: 24htotal, current total, period, timing volume, supports history rate review

## Syringes

Compatibility 1/2/3/5/6/10/12/20/30/35/50/60ml, automatic recognition of syringe size

## Alarms

Type Audible and visual alarm

2Levels High: Occlusion/ Syringe Empty/ Syringe

Disengaged/ Plunger Grippers  
Error/Battery Depleted/ VTBI Complete/  
Invalid KVO Finish/ Relay / System Error/  
No Syringe

Low: Extension Line Detached/ KVO  
Running/ Battery in Use/ Battery  
Error/CMS/eGW Disconnected/ Standby  
Time Expired/ Dock Connection  
Interrupted/ System Time Error/ Relay  
Invalid Soon/ Time Near End/ Reminder/  
Low Battery/ Syringe Near Empty

Sound volume 1-8 levels selectable, default is level 6  
Reminder 1-5 minutes selectable,  
ON/OFF switchable

## Connectivity

Communication Wired/wireless  
USB Support drug library import, patient data  
import/export, history record export,  
calibration data import/export  
Multifunctional RS232,nurse call connector, DC adapter  
connector  
Integration Connect with CMS Vet central station

## Battery

Operating time  $\geq 5$  hours at 5ml/h ( $\geq 11$  hours at 5ml/h for  
smartbattery)  
Charging time  $\leq 5$  hours to full capacity ( $\leq 6$  hours for  
smartbattery)

## Power Supply

Voltage 100-240 V~,frequency 50/60Hz,current 0.5-0.21A

## Work Environment

Temperature 5-40°C for operating,-30-70 °C for storage

Relative humidity 15-95% for operating, 10-95% for storage

Atmosphere pressure 57.0-107.4 kPa for operating, 16.0-107.4  
kPa for storage

Classification Type CF, Class I, IP33

Stackability Supported with stack rack, maximum of 3  
pumps can be stacked

[www.mindrayaniaml.com](http://www.mindrayaniaml.com)

©2021 Shenzhen Mindray Animal Medical Technology Co., LTD. All rights reserved.

